

## 多路程控电源产品选购指南

产品型号	MPD-3303C	MPD-3305C	MPD-3303	MPD-3305	MPD-3303D	MPD-3305D	MPD-3303S
功能特点							
0~30V/3A×2	√	—	√	—	√	—	√
0~30V/5A×2	—	√	—	√	—	√	—
2.5V/3.3V/5V/3A×1	√	√	√	√	√	√	√
分辨率	100mV/10mA	100mV/10mA	10mV/10mA	10mV/10mA	100mV/10mA	100mV/10mA	1mV/1mA
电压表	3 digits LED	3 digits LED	3 digits LED	3 digits LED	3 digits LED	3 digits LED	5 digits LED
电流表	3 digits LED	3 digits LED	3 digits LED	3 digits LED	3 digits LED	3 digits LED	4 digits LED
恒压/恒流操作	√	√	√	√	√	√	√
串联/并联操作	√	√	√	√	√	√	√
输出打开/关闭控制	√	√	√	√	√	√	√
数字面板控制	√	√	√	√	√	√	√
保存/呼叫	4 sets	4 sets	4 sets	4 sets	4 sets	4 sets	4 sets
粗调与细调电压/电流	√	√	√	√	√	√	√
按键锁定功能	√	√	√	√	√	√	√
蜂鸣输出	√	√	√	√	√	√	√
软件校准	√	√	√	√	√	√	√
温控风扇	√	√	√	√	√	√	√
过载保护	√	√	√	√	√	√	√
极性反向保护	√	√	√	√	√	√	√
USB接口	—	—	—	—	√	√	√