

单路程控电源产品选购指南

产品型号	MPM-3003S	MPM-3005S	MPD-3003S	MPD-3005S	MPD-6001S	MPD-6003S	MPD-6005S	MPD-2010S	MPD-3010S	MPD-7503S	MPD-7505S
功能特点											
输出量程	双量程	双量程	单量程	单量程	单量程	单量程	单量程	单量程	单量程	单量程	单量程
输出额定值	0~36V/3A or 0~15V/6A	0~36V/5A or 0~15V/10A	0~30V/3A	0~30V/5A	0~60V/1A	0~60V/3A	0~60V/5A	0~20V/10A	0~30V/10A	0~75V/3A	0~75V/5A
分辨率	1mV/0.1mA	1mV/1mA	1mV/0.1mA	1mV/0.1mA	1mV/0.1mA	1mV/0.1mA	1mV/0.1mA	1mV/1mA	1mV/1mA	2mV/0.1mA	2mV/0.1mA
显示方式	LCD	LCD	LCD	LCD	LCD	LCD	LCD	LCD	LCD	LCD	LCD
恒压/恒流操作	√	√	√	√	√	√	√	√	√	√	√
输出打开/关闭控制	√	√	√	√	√	√	√	√	√	√	√
保存/呼叫	100组	100组	100组	100组	100组	100组	100组	100组	100组	100组	100组
粗调与细调电压/电流	√	√	√	√	√	√	√	√	√	√	√
按键锁定功能	√	√	√	√	√	√	√	√	√	√	√
定时输出功能	√	√	√	√	√	√	√	√	√	√	√
数字按键控制	√	√	√	√	√	√	√	√	√	√	√
蜂鸣输出	√	√	√	√	√	√	√	√	√	√	√
软件校准	√	√	√	√	√	√	√	√	√	√	√
温控风扇	√	√	√	√	√	√	√	√	√	√	√
过载保护	√	√	√	√	√	√	√	√	√	√	√
极性反向保护	√	√	√	√	√	√	√	√	√	√	√
过压保护	√	√	√	√	√	√	√	√	√	√	√
过流保护	√	√	√	√	√	√	√	√	√	√	√
过温保护	√	√	√	√	√	√	√	√	√	√	√
USB接口	√	√	√	√	√	√	√	√	√	√	√
RS232接口	√	√	√	√	√	√	√	√	√	√	√

注：USB与RS232接口无法并存