

PRODUCT SELECTION GUIDE

Multi-output Programmable DC Power Supply

MODEL FUNCTION	MPD-3303C	MPD-3305C	MPD-3303	MPD-3305	MPD-3303D	MPD-3305D	MPD-3303S
0~30V/3A×2	√	—	√	—	√	—	√
0~30V/5A×2	—	√	—	√	—	√	—
2.5V/3.3V/5V/3A×1	√	√	√	√	√	√	√
Resolution	100mV/10mA	100mV/10mA	10mV/10mA	10mV/10mA	100mV/10mA	100mV/10mA	1mV/1mA
Voltmeter	3 digits LED	3 digits LED	3 digits LED	3 digits LED	3 digits LED	3 digits LED	5 digits LED
Ammeter	3 digits LED	3 digits LED	3 digits LED	3 digits LED	3 digits LED	3 digits LED	4 digits LED
CV/CC operation	√	√	√	√	√	√	√
Tracking series/tracking parallel operation	√	√	√	√	√	√	√
Output on/off	√	√	√	√	√	√	√
Digital panel control	√	√	√	√	√	√	√
Save/recall	4 sets	4 sets	4 sets	4 sets	4 sets	4 sets	4 sets
Coarse and fine control for voltage/current	√	√	√	√	√	√	√
Key lock function	√	√	√	√	√	√	√
Beeper output	√	√	√	√	√	√	√
Software calibration	√	√	√	√	√	√	√
Intelligent cooling fan	√	√	√	√	√	√	√
Overload protection	√	√	√	√	√	√	√
Reverse polarity protection	√	√	√	√	√	√	√
USB interface	—	—	—	—	√	√	√